

CEMSEAL KRACKFILL

Non-shrink, High Strength Crack Filling Powder

DESCRIPTION

A non-shrink, high strength crack filling powder for surface cracks in plaster. CEMSEAL KRACKFILL powder is a specially formulated cement based polymer modified powder for filling cracks in plastered surfaces. Powder when mixed with water forms a creamy consistent paste which is easy to use for filling cracks in plastered surfaces.

AREA OF APPLICATION

Repairing of internal and external cracks in plastered surfaces.

METHOD OF APPLICATION

- Widen the crack by cutting the plaster in "V" shape around the crack. Clean the crack to remove all loose material. Ensure the surface is free from oil, dust and grease.
- Mix CEMSEAL KRACKFILL powder in CEMSEAL KRACKFILL+ in proportion 2.5 part CEMSEAL KRACKFILL powder to 1 part of CEMSEAL KRACKFILL+ by volume.
- CEMSEAL KRACKFILL+ can be replaced by water if unavailable.
- Moisten the surface slightly before applying CEMSEAL KRACKFILL powder
- Press CEMSEAL KRACKFILL powder paste into the cracks using a spatula or putty knife. Level the surface with a putty knife to get a smooth & clean surface. Painting operation can start after 24 hour when CEMSEAL KRACKFILL powder is completely cured.

FEATURES & BENEFITS

- Accommodates movements in the cracks.
- Universal stainer can be mixed with crack filler.
- Overcoatable after curing.
- Single component and needs only mixing with CEMSEAL KRACKFILL+ or water.
- Replaces costly sealants and putties.
- No Shrinkage.
- Excellent adhesion

TECHNICAL INFORMATION

- **Shelf Life** : 12 Months
- **Coverage** : Approx 60 RFT/KG for 5 mm x 5 mm crack
- **Nature** : White coloured powder
- **Storage** : Store in a cool and dry place



PRECAUTIONS & LIMITATIONS

- CEMSEAL KRACKFILL powder, is strictly not recommended to fill cracks more than 5mm.
- Strictly not for filling expansion joints / construction joints
- Painting should commence after minimum 24 hours

PACKAGING

1 KG & 20 KG

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately.

If accidentally ingested, seek immediate medical attention. Reseal containers after use.

TECHNICAL INFORMATION & SERVICES

Further information and advice including practical demonstration are freely available from the technical service department of Cemseal Industries Ltd.

NOTE

- Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Cemseal representative.
- Cemseal reserves the right to have the true cause of any difficulty determined by accepted test methods.

Address

Plant 1 : C-1/B-96-97 G.I.D.C Industrial Estate, Kalol, Panchmahal, Gujarat - 389330

Plant 2 : Plot no 30, Marble Market Sejbahar, Rajpur, Chhattisgarh - 492015

Web : www.cemseal.net | **Contact no** : +91 90992 66166