

CEMCOAT

Interior / Exterior Acrylic
Wall Emulsion

DESCRIPTION

CEMCOAT is a rapid drying solvent free low VOC water based acrylic wall solution for Interior & Exterior walls. CEMCOAT is compatible with cement based ceramic tile, too. CEMCOAT can be used as primer & paint.

BENEFITS

- Makes surface durable.
- Prepares wall for finish coats.
- Provides extended paint coverage.
- Provides smoother finish appearance.
- Can be tinted with any colour with white base.
- Any customized colour can be directly provided by factory, if required in bulk.

SUBSTRATES

CEMCOAT can be applied internally or externally over clean dry wall surfaces.

SURFACE PREPARATION

- Surface must be free from oil, grease, wax, curing compounds, dust, old adhesive and any other contamination, which may inhibit bond.

Note:

- Surface must be dry
- Works well above 5 Degree Celsius. For temperatures below it, kindly contact our technical team.

APPLICATION

- Interior and exterior walls
- Wood trims, doors, and flooring
- Windows
- Stairs
- Surfaces like wicker, masonry, concrete & plaster.

FEATURES

- Mixing : Thoroughly mix well CEMCOAT before use.
Clean up : Clean all equipments with water immediately after use.
Coverage : As Primer : 6 to 8 square metres per litre per coat
As Paint : 4 to 6 square metres per litre per coat
Packaging : Ltr - 1, 4, 10, 20



Shelf life	: 12 months from date of manufacturing in unopened containers.
Storage	: CEMCOAT must be stored in a dry area off the ground, out of direct sun light, protect from Frost.
Initial Curing Time	: 1-2 hours @ 25°C in dry weather .
Final Curing Time	: 48 hours @25 degree
Recoating Time	: Minimum 8 hours after previous coat
Restrictions	A) Do not apply CEMCOAT on substrates subject to rising damp. B) Do not apply CEMCOAT on tiles that have wax or excessively high gloss coating

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

TECHNICAL INFORMATION & SERVICES

Further information and advice including practical demonstration are freely available from the technical service department of CEMSEAL INDUSTRIES LTD.

NOTE

- Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Cemseal representative.
- Cemseal reserves the right to have the true cause of any difficulty determined by accepted test methods.

Address

Plant 1 : C-1/B-96-97 G.I.D.C Industrial Estate, Kalol, Panchmahal, Gujarat - 389330

Plant 2 : Plot no 30, Marble Market Sejbahar, Rajpur, Chhattisgarh - 492015

Web : www.cemseal.net | **Contact no** : +91 90992 66166