

CEMCOAT

Eco-Acrylic Emulsion - Interior / Exterior

DESCRIPTION

CEMCOAT is a solvent free low VOC water based acrylic wall emulsion for Interior & Exterior walls. CEMCOAT is compatible with cement based ceramic tile, too.

BENEFITS

- Makes surface durable.
- Provides anti-fade protection for long-lasting colour, low maintenance.
- Offers superior washability compared to distemper, keeping walls looking their best with ease.
- Provides smoother finish appearance & matt finish.
- Can be used as a regular/coloured primer as well by adjusting the water mixing ratio.
- Can be tinted with any colour with white base.

SUBSTRATES

CEMCOAT can be applied internally or externally over clean dry wall surfaces.

SURFACE PREPARATION

- Surface must be free from oil, grease, wax, curing compounds, dust, old adhesive and any other contamination, which may inhibit bond.
- **Note:**
- Surface must be dry
- Works well above 5 Degree Celsius. For temperatures below it, kindly contact our technical team.

APPLICATION

- Interior and exterior walls
- Windows
- Stairs
- Surfaces like wicker, masonry, concrete & plaster.
- Wood trims, doors, and flooring

FEATURES

Mixing	: Thoroughly mix well after adding DM water before use. For use as a Primer: add up to 20% DM water For use as an Emulsion: add up to 10% DM water
Shelf life	: 12 months from date of manufacturing in sealed containers.
Coverage	: As a Primer : 60 to 80 square ft. per litre per coat. As an Emulsion : 40 to 60 square ft. per litre per coat.
Initial Curing Time	: 1-2 hours @ 25°C in dry weather.
Final Curing Time	: 48 hours @25°C.
Recoating Time	: Minimum 8 hours after previous coat
Storage	: CEMCOAT must be stored in a dry area off the ground, out of direct sun light, protect from Frost.
Restrictions	:A) Do not apply CEMCOAT on substrates subject to rising damp. B) Do not apply CEMCOAT on tiles that have wax or excessively high gloss coating.
Clean up	: Clean all the equipments with water immediately after use.
Packaging	: Ltr – 1, 4, 10, 20





...Building on over 200 years' experience

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

TECHNICAL INFORMATION & SERVICES

Further information and advice including practical demonstration are freely available from the technical service department of CEMSEAL INDUSTRIES LTD.

NOTE

- Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Cemseal representative.
- Cemseal reserves the right to have the true cause of any difficulty determined by accepted test methods.

Address

Plant 1 : C-1/B-96-97 G.I.D.C Industrial Estate, Kalol, Panchamahar, Gujarat - 389330

Plant 2 : Plot no 30, Marble Market Sejbahar, Rajpur, Chhattisgarh - 492015

Web : www.cemseal.net | **Contact no** : +91 90992 66166