

WOODY WOODSOL

Water Resistant Wood Primer With Anti Termite Formula

DESCRIPTION

Water Based WOODSOL:

WOODSOL is an anti terminate formula to protect wood from swelling. It helps preventing blistering on wood. It penetrates, seals & fills the wood fiber & gives a very good adhesion to surface. Finished solution can be applied easily without absorbing and prevents from weather. Provides excellent adhesion. It conforms to IS 101/1987 part 1, Section 6.

PRODUCT DATA

Recommended Use	: Surface plywood, black board wood, pressed wood
Finish	: Semi matt
Colour	: White
Covering Capacity	: On smooth surface : 130 to 150 sq.ft/ltr/coat for 15 micron dry film thickness depending upon surface by brush
Drying Time	: Single Coat at Standard thickness: Touch Dry : 4-6 hours, Recoat : 16-24 hours
Thinner recommended	: DM Water

APPLICATION VISCOSITY

Brushing - 45 to 50 sec at 30° C by FC No 4
Spraying - 25 to 30 sec at 30° C by FC No 4

METHOD OF APPLICATION

By brush or spray at a pressure of 40 to 50 PSI.

SUBSEQUENT COAT

- Remove enamels, under surface dust, oil, grease, loose flakes. Apply one or two layer by adjusting the viscosity with recommended thinner. Allow wood layer to hard dry. Dry cut with sand paper before applying subsequent layer. Stir well prior to use.
- Treat any knots in wood with an appropriate knotting solution.

TRANSPORTATION & STORAGE

Do not use or store in extreme temperatures and protect from frost. To prevent spillage, please store and transport upright.



SAFETY PRECAUTIONS

- As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and food stuffs.
- Treat splashes to eyes and skin immediately.
- If accidentally ingested, seek immediate medical attention. Reseal containers after use.

TECHNICAL INFORMATION & SERVICES

Further information and advice including practical demonstration are freely available from the technical service department of Cemseal Industries Ltd.

NOTE

- Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Cemseal representative.
- Cemseal reserves the right to have the true cause of any difficulty determined by accepted test methods.

Address

Plant 1 :C-1/B-96-97 G.I.D.C Industrial Estate, Kalol, Panchamahar, Gujarat - 389330

Plant 2 :Plot no 30, Marble Market Sejbahar, Rajpur, Chhattisgarh - 492015

Web : www.cemseal.net | **Contact no** : +91 90992 66166