

UNISOL

Interior / Exterior Acrylic
Wall Primer

DESCRIPTION

UNISOL is a solvent free & low VOC water based acrylic wall primer for Interior & Exterior walls. UNISOL is compatible with cement based ceramic tile, too.

BENEFITS

- Makes surface durable.
- Provides extended paint coverage.
- Prepares wall for finish coats.
- Provides smoother finish appearance.

SUBSTRATES

UNISOL can be applied internally or externally over clean dry wall surfaces.

SURFACE PREPARATION

- Surface must be free from oil, grease, wax, curing compounds, dust, old adhesive and any other contamination, which may inhibit bond.
- **Note:**
- Surface must be dry
- Works well above 5 Degree Celsius. For temperatures below it, kindly contact our technical team.

APPLICATION

- Interior and exterior walls
- Surfaces like wicker, masonry, concrete & plaster.
- Stairs

FEATURES

Mixing	: Thoroughly mix well after adding up to 20% DM water before use.
Storage	: UNISOL must be stored in a dry area off the ground, out of direct sun light, protect from Frost.
Restrictions	:A) Do not apply UNISOL on substrates subject to rising damp. B) Do not apply UNISOL on tiles that have wax or excessively high gloss coating.
Shelf life	: 12 months from date of manufacturing in sealed containers.
Clean up	: Clean all equipments with water immediately after use.
Coverage	:70 to 80 square feet per litre per coat.
Initial Curing Time	: 1-2 hours @ 25°C in dry weather.
Final Curing Time	:48 hours @25°C.
Recoating Time	:Minimum 8 hours after previous coat
Packaging	: Ltr – 1, 4, 10, 20





...Building on over 200 years' experience

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

TECHNICAL INFORMATION & SERVICES

Further information and advice including practical demonstration are freely available from the technical service department of CEMSEAL INDUSTRIES LTD.

NOTE

- Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Cemseal representative.
- Cemseal reserves the right to have the true cause of any difficulty determined by accepted test methods.

Address

Plant 1 : C-1/B-96-97 G.I.D.C Industrial Estate, Kalol, Panchamahar, Gujarat - 389330

Plant 2 : Plot no 30, Marble Market Sejbahar, Rajpur, Chhattisgarh - 492015

Web : www.cemseal.net | **Contact no** : +91 90992 66166